

Exercise 4: Optimal Control with Single Shooting

Andrea Zanelli, Joel Andersson, Joris Gillis, Sebastien Gros, Moritz Diehl

In this exercise we will start working with Optimal Control Problems (OCP). In particular, we will solve the following continuous-time infinite dimensional problem:

$$\begin{aligned} \min_{x,u} \quad & \int_0^T x(t)^2 + u(t)^2 dt \\ \text{s.t.} \quad & \dot{x} = (1+x)x + u \\ & |u(t)| \leq 0.075 \\ & x(0) = \bar{x}_0 \\ & x(T) = 0, \end{aligned}$$

where $u \in \mathbb{R}$ is the control input and $x \in \mathbb{R}$ is the state of the system, $T = 3$ and $\bar{x}_0 = 0.05$. The above formulation can be discretized by integrating the dynamics of the system over a fixed grid with $N + 1$ nodes leading to the finite-dimensional discrete-time problem

$$\begin{aligned} \min_{\substack{x_0, \dots, x_N \\ u_0, \dots, u_{N-1}}} \quad & h \sum_{i=0}^{N-1} (x_i^2 + u_i^2) + x_N^2 \\ \text{s.t.} \quad & x_{i+1} = f(x_i, u_i), \quad i = 0, \dots, N-1 \\ & |u_i| \leq 0.075, \quad i = 0, \dots, N-1, \\ & x_0 = \bar{x}_0 \\ & x_N = 0, \end{aligned} \tag{1}$$

where f describes the discretized dynamics obtained using an integration scheme, $h := \frac{T}{N}$, x_i and u_i refer to the evaluation of state and control trajectories, respectively, where x_i correspond to the discretization nodes:

$$x_i = x(ih), \quad i = 0, \dots, N. \quad i = 0, \dots, N-1.$$

It is possible to eliminate the state variables from (2) by exploiting the equality constraints obtaining a more compact form:

$$\begin{aligned} \min_{u_0, \dots, u_{N-1}} \quad & \Phi(u) \\ \text{s.t.} \quad & |u_i| \leq 0.075, \quad i = 0, \dots, N-1, \\ & x_N(u) = 0, \end{aligned} \tag{2}$$

where $\Phi(u) := h(\bar{x}_0^2 + u_0^2 + f(\bar{x}_0, u_0)^2 + u_1^2 + \dots)$. This approach is the so called *single shooting* scheme.

4.1 Implement a CasADi Function f that takes as argument the states x and input u and returns the ODE right-hand-side \dot{x} .

4.2 Divide the time horizon into $N = 30$ equidistant control intervals, then use the RK4 scheme to define the discrete-time dynamics as a CasADi function. This function should take $x(t_i)$ and u_i as inputs and return $x(t_{i+1})$. The key lines of the integrator implementation could look like this:

```
1 out = f({X,U});
2 k1 = out{1};
3 % ...
4 X = X + h/6*(k1 + 2*k2 + 2*k3 + k4);
```

4.3 Formulate the direct single shooting NLP and solve it with IPOPT. Note that the NLP should have N degrees of freedom, so start by defining a variable $u \in \mathbb{R}^N$:

```
1 u = SX.sym('u',N);
```

The key lines of the NLP formulation could look like this:

```
1 X = X0;
2 for i = 1:N
3     out = F({X,v(i)});
4     X = out{1};
5     J = J + X(1)^2 + u(i)^2;
6 end
```

4.4 Introduce the additional path constraints $x_i \geq 0.05$, $i = 15, \dots, 17$. Change your scripts to solve the modified problem.

4.5 **Extra:** Replace the dynamics in the NLP from Task 4.4 with their linearization at the origin $x_0 = 0$. Compute the optimal solution and apply it to the original system. Are the path constraints satisfied? Is there a neighborhood of the origin where this linearized optimal control problem will provide a feasible solution?